


## Cuscinetti conico 2984-2925-TIMKEN - 2984-2925-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/2984-2925-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(3)</sup> C <sub>2e</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N	N	N			
46.037	87.312	26.988	3230	1.73	5420	16300	1.68	117000	2984	2925
1.8125	3.4375	1.0625	21000		5440	3220		20000		

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage				
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>s</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	A <sub>3</sub> <sup>(3)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	
26.988	22.225	-4.4	3.5	52.8	58.8	2.3	81.8	75.8	1.7	1.1	36.2	15.7	0.9832	6.88
1.0625	0.8750	-0.25	0.14	2.05	2.31	0.09	3.19	2.95	0.07	0.05			1.90	

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952314990
Diametro interno	46.037 mm
Diametro interno	1 13/16" inch
Diametro esterno	87.312 mm
Diametro esterno	3 7/16" inch
Spessore	26.988 mm
Spessore	1 1/16" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE