


## Cuscinetti conico 750A-742-TIMKEN - 750A-742-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/750a-742-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>0</sub>	Factor <sup>(2)</sup> K	Static C <sub>0</sub>	Inner	Outer
mm	mm	mm	N		N		N		N		
82.550	150.089	44.450	37900	3.33	124	6700	9400	1.82	41700	750A	742
3.2530	5.9050	1.7500	84700		21900		12200		53600		

Bearing Dimensions										Geometry Factors			Bearing Weight
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>f1</sub>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
46.672	36.932	-11.9	0.5	103.6	106.6	3.3	142.8	134.8	1.8	1.3	159.6	26.3	0.9888
1.8375	1.4375	-0.47	0.20	3.88	4.17	0.13	5.59	5.28	0.07	0.05		3.33	

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952322469
Diametro interno	82.55 mm
Diametro esterno	150.089 mm
Spessore	44.45 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE