


## Cuscinetti conico 6581X-6535-TIMKEN - 6581X-6535-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/6581x-6535-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                         |                        |                                       |                        |                       |       | Part Number |  |
|--------------------|---------|---------|--------------------------------------|------------------------|---------------------------------------|------------------------|-----------------------|-------|-------------|--|
| Bore d             | O.D. D  | Width B | Dynamic <sup>10</sup> C <sub>1</sub> | Factor <sup>11</sup> e | Dynamic <sup>10</sup> C <sub>02</sub> | Factor <sup>10</sup> K | Static C <sub>0</sub> | Inner | Outer       |  |
| mm                 | mm      | mm      | N                                    |                        | N                                     |                        | N                     |       |             |  |
| 90                 | 161.925 | 53.975  | 42900                                | 1.52                   | 114000                                | 1.46                   | 52300                 | 6581X | 6535        |  |
| 2.193              | 6.376   | 2.126   | 9800                                 |                        | 2500                                  |                        | 11800                 |       |             |  |

| Bearing Dimensions |         |                         |   |                                      |                                      |   |                                      |                                      |                                   | Geometry Factors                  |                |                | Bearing Weight |                |
|--------------------|---------|-------------------------|---|--------------------------------------|--------------------------------------|---|--------------------------------------|--------------------------------------|-----------------------------------|-----------------------------------|----------------|----------------|----------------|----------------|
| Width B            | Width C | ER. Dr. a <sup>10</sup> | Max Shaft Fillet Radius R <sup>11</sup> | Backing Shoulder Dia. d <sub>1</sub> | Backing Shoulder Dia. d <sub>2</sub> | Max Housing Fillet Radius r <sup>11</sup> | Backing Shoulder Dia. D <sub>1</sub> | Backing Shoulder Dia. D <sub>2</sub> | Cage A <sub>1</sub> <sup>10</sup> | Cage A <sub>2</sub> <sup>10</sup> | G <sub>1</sub> | G <sub>2</sub> |                | C <sub>3</sub> |
| mm                 | mm      | mm                      | mm                                      | mm                                   | mm                                   | mm  | mm                                   | mm                                   | mm                                | mm                                |                |                |                | kg             |
| 53.975             | 42.862  | -13.2                   | 3.8                                     | 102.0                                | 105.8                                | 3.3                                       | 154.8                                | 161.8                                | 4.1                               | 8.8                               | 108.6          | 33.5           | 0.1037         | 4.64           |
| 2.193              | 1.6875  | -0.52                   | 0.12                                    | 4.02                                 | 4.23                                 | 0.13                                      | 6.09                                 | 5.59                                 | 0.16                              | 0.04                              |                |                |                | 10.22          |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952323268 |
| Diametro interno | 90 mm         |
| Diametro esterno | 161.925 mm    |
| Spessore         | 53.975 mm     |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE