


## Cuscinetti conico 938-930-TIMKEN - 938-930-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/938-930-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |         |         | Load Ratings                             |                            |                                          |                            |                          |       | Part Number |  |
|--------------------|---------|---------|------------------------------------------|----------------------------|------------------------------------------|----------------------------|--------------------------|-------|-------------|--|
| Bore d             | O.D. D  | Width T | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factor <sup>(2)</sup><br>Y | Dynamic <sup>(1)</sup><br>C <sub>2</sub> | Factor <sup>(2)</sup><br>X | Static<br>C <sub>0</sub> | Inner | Outer       |  |
| mm                 | mm      | mm      | N                                        |                            | N                                        |                            | N                        |       |             |  |
| 114.300            | 206.375 | 66.675  | 127000                                   | 1.24                       | 148000                                   | 1.78                       | 280000                   | 528   | 528         |  |
| 4.5000             | 8.1250  | 2.6250  | 126000                                   |                            | 33000                                    | 18000                      | 173000                   |       |             |  |

| Bearing Dimensions |         |                          |                                         |                                      |                                          |                                      |                                    |                               |                | Geometry Factors |                |      | Bearing Weight |       |
|--------------------|---------|--------------------------|-----------------------------------------|--------------------------------------|------------------------------------------|--------------------------------------|------------------------------------|-------------------------------|----------------|------------------|----------------|------|----------------|-------|
| Width B            | Width C | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sub>f1</sub> | Backing Shoulder Dia. d <sub>s</sub> | Max Housing Fillet Radius r <sub>1</sub> | Backing Shoulder Dia. D <sub>s</sub> | Cage A <sub>1</sub> <sup>(1)</sup> | A <sub>2</sub> <sup>(1)</sup> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>1</sub> |      |                |       |
| mm                 | mm      | mm                       | mm                                      | mm                                   | mm                                       | mm                                   | mm                                 | mm                            |                |                  |                | kg   |                |       |
| 66.675             | 63.875  | -16.8                    | 7.8                                     | 128.0                                | 141.8                                    | 3.3                                  | 153.1                              | 184.0                         | 6.6            | 1.3              | 338.6          | 30.8 | 0.1103         | 6.88  |
| 2.6250             | 2.1250  | -0.78                    | 0.28                                    | 5.04                                 | 5.55                                     | 0.13                                 | 7.80                               | 7.24                          | 0.26           | 0.05             |                |      |                | 19.79 |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952324647 |
| Diametro interno | 114.3 mm      |
| Diametro esterno | 206.375 mm    |
| Spessore         | 66.675 mm     |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE