


Cuscinetti a sfera fila unica ZKLN1545-2Z-INA - ZKLN1545-2Z-INA


<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/zkln1545-2z-ina>

Axial angular contact ball bearings ZKLN1545-2Z
double direction, gap seats on both sides



d	15 mm	Tolerance: -0.005
D	45 mm	Tolerance: -0.010
B	25 mm	Tolerance: -0.25
α	60 °	Contact angle
D _{max}	35 mm	
d ₁	28 mm	
d ₂	20 mm	
r _{1 max}	0.6 mm	
r _{2 max}	0.3 mm	
m	0.21 kg	Mass
C _d	17900 N	Basic dynamic load rating, axial
C _a	9500 N	Basic static load rating, axial
n _{Grease}	7500 1/min	Limiting speed for grease lubrication
M _{fr}	0.8 Nm	Bearing frictional torque
Δi	±0.020 N/mm	Axial rigidity
Δα	60 N/m/rad	Tilting rigidity
M _r	0.102 kg x cm ²	Mass moment of inertia for rotating inner ring
σ _a	2 μm	Axial runout
ZM15		Designation of recommended INA locknut
AM15		Designation of recommended INA locknut
M _t	10 Nm	Tightening torque
F _{ax}	5484 N	Axial preload force

Design of adjacent construction



CARATTERISTICHE DEL PRODOTTO

Marchio	INA
N° Ean13	3663952334851
Diametro interno	15 mm
Impermeabilizzazione	Schermo su entrambi i lati
Diametro esterno	45 mm
Spessore	25 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE