




## Cuscinetti a sfera fila unica ZKLN1747-2Z-INA - ZKLN1747-2Z-INA

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/zkln1747-2z-ina>

**Axial angular contact ball bearings ZKLN1747-2Z**  
double direction, gap seats on both sides

d	17 mm	Tolerance: -0,006
D	47 mm	Tolerance: -0,010
B	25 mm	Tolerance: -0,20
	60 °	Contact angle
D <sub>1max</sub>	37 mm	
d <sub>1</sub>	30 mm	
d <sub>1s</sub>	23 mm	
f <sub>1max</sub>	0,6 mm	
f <sub>1s</sub>	0,3 mm	
m	0,22 kg	Mass
C <sub>a</sub>	18500 N	Basic dynamic load rating, axial
C <sub>0a</sub>	31000 N	Basic static load rating, axial
n <sub>0,grease</sub>	6600 1/min	Limiting speed for grease lubrication
M <sub>fr</sub>	0,92 Nm	Bearing frictional torque
C <sub>a</sub>	450 N/μm	Axial rigidity
α	60 Nm/rad	Tilting rigidity
M <sub>J</sub>	0,132 kg x cm <sup>2</sup>	Mass moment of inertia for rotating inner ring
	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZM17	Designation of recommended INA locknut
	AM17	Designation of recommended INA locknut
		Locknuts not included in delivery.
M <sub>A</sub>	15 Nm	Tightening torque
		Only valid in conjunction with INA precision locknuts
	7157 N	Axial preload force

### CARATTERISTICHE DEL PRODOTTO

Marchio	INA
N° Ean13	3663952334868
Diametro interno	17 mm
Impermeabilizzazione	Schermo su entrambi i lati
Diametro esterno	47 mm
Spessore	25 mm
Peso	220 g
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE