




Cuscinetti a sfera fila unica ZKLN50110-2Z-INA - ZKLN50110-2Z-INA

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera-fila-unica/zkln50110-2z-ina>

Axial angular contact ball bearings ZKLN50110-2Z
double direction, gap seals on both sides

d	50 mm	Tolerance: -0.005
D	110 mm	Tolerance: -0.01
B	54 mm	Tolerance: -0.25
α	60 °	Contact angle
D_{dmax}	58 mm	
d_1	60 mm	
d_2	63 mm	
r_{1max}	0,6 mm	
r_{2max}	0,6 mm	
Hobby series		
m	2,6 kg	Mass
C_2	13200 N	Basic dynamic load rating, axial
C_0	229000 N	Basic static load rating, axial
$n_{G,ref}$	2000 1/min	Limiting speed for grease lubrication
M_{fr}	1,5 Nm	Bearing frictional torque
C_{02}	1400 N/mm	Axial rigidity
S_{02}	1500 N/mmrad	Tilting rigidity
M_{02}	19,2 kg x cm ²	Mass moment of inertia for rotating inner ring
	2,5 μm	Axial runout
	The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.	
ZMAS075	Designation of recommended INA locknut	
AMS0	Designation of recommended INA locknut	
	Locknuts not included in delivery.	
M_{fr}	150 Nm	Tightening torque
	Only valid in conjunction with INA precision locknuts	
	29436 N	Axial preload force

Design of adjacent construction

Design of adjacent construction

CARATTERISTICHE DEL PRODOTTO

Marchio	INA
N° Ean13	3663952334950
Diametro interno	50 mm
Impermeabilizzazione	Schermo su entrambi i lati
Diametro esterno	110 mm
Spessore	54 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE