


Cuscinetti conico 2796-2720-B-TIMKEN - 2796-2720-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/2796-2720-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₀ | Factors ⁽²⁾ K | Static C ₂ | Inner | Outer |
| mm | mm | mm | N | | | N | | N | | |
| 34.925 | 76.200 | 11.112 | 8000 | 0.30 | 1.91 | 22500 | 11300 | 102000 | 2796 | 2720 B |
| 1.3750 | 3.0000 | 0.4375 | 19000 | | | 5000 | 2830 | 25000 | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|--|------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. d ₃ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₃ | | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | lb | |
| 25.004 | 19.000 | 4.11 | 60.598 | 6.200 | 3.5 | 41.6 | 43.5 | 73.0 | 29.7 | 12.2 | 0.0125 | | 0.59 | |
| 1.0100 | 0.7500 | -0.32 | 2.3900 | 0.2400 | 0.14 | 1.61 | 1.67 | 2.87 | | | | | 1.29 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952336145 |
| Diametro interno | 34.925 mm |
| Diametro esterno | 76.2 mm |
| Spessore | 11.112 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE