


Cuscinetti conico 444-432AB-TIMKEN - 444-432AB-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/444-432ab-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|--|-----------------------------|--------------------------|-------|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 38.130 | 92.075 | 11.115 | 127800 | 0.25 | 32900 | 1000 | 14800 | 444 | 432AB | |
| 1.500 | 3.620 | 0.4376 | 2630 | | 740 | 360 | 3240 | | | |

| Bearing Dimensions | | | | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|------------------|----------------|--|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₁ | | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | lbs |
| 11.115 | 22.225 | -4.1 | 97.526 | 9.508 | 3.3 | 46.3 | 52.9 | 67.9 | 42.9 | 11.3 | 0.085 | | 0.96 |
| 0.4376 | 0.8752 | -0.16 | 3.8400 | 0.2188 | 0.14 | 1.79 | 2.05 | 2.63 | | | | | 2.18 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952336435 |
| Diametro interno | 38.1 mm |
| Diametro esterno | 92.075 mm |
| Spessore | 11.115 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE