


Cuscinetti conico 2973-2924-B-TIMKEN - 2973-2924-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/2973-2924-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|---|-----------------------------|---|-----------------------------|--------------------------|-------|--------|-------------|--------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁₀ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₉₀ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | | |
| mm | mm | mm | N | | N | | N | | | | |
| 42.862 | 85.000 | 25.608 | 22360 | 0.25 | 1.70 | 24200 | 14300 | 1.89 | 113000 | 2973 | 2924-B |
| 1.6875 | 3.3465 | 0.2750 | 21000 | | 5440 | | 3220 | | 26200 | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. d ₂ | Sealing Shoulder Dia. D ₁ | D ₂ | D ₃ | C ₁ | C ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | mm |
| 25.608 | 25.508 | -4.4 | 88.764 | 4.762 | 3.5 | 46.5 | 66.0 | 62.0 | 28.2 | 15.7 | 0.002 | 0.002 | 0.002 | 0.66 |
| 1.0082 | 0.8125 | -0.25 | 3.5040 | 0.1875 | 0.14 | 1.80 | 2.20 | 2.23 | | | | | | 1.53 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952336985 |
| Diametro interno | 42.862 mm |
| Diametro esterno | 85 mm |
| Spessore | 25.608 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE