


Cuscinetti conico 6464-6420-B-TIMKEN - 6464-6420-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/6464-6420-b-timken>

TAPERED ROLLER BEARINGS
TYPE TSF



| Bearing Dimensions | | | | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|------|--|----------------------------|--------------------------|-------|--------|--|-------------|--|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₀ | Factor ⁽³⁾ K | Static C ₀ | Inner | Outer | | | |
| mm | mm | mm | N | | | N | | N | | | | | |
| 64.96 | 149.225 | 54.229 | 411000 | 0.30 | 1.91 | 107000 | 50000 | 143000 | 6464 | 6420 B | | | |
| 2.5575 | 5.8750 | 2.1350 | 50400 | | | 24000 | 14000 | 194000 | | | | | |

| Bearing Dimensions | | | | | | Shaft | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|------------------------------------|-----------------------------------|--|--|--|--|----------------|----------------|------------------|------|-------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽⁴⁾ | Outer Ring Range D ₁ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁵⁾ | Seaking Shoulder Dia. d ₂ | Seaking Shoulder Dia. d ₃ | Seaking Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₂ | | | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm |
| 54.229 | 44.450 | -15.0 | 107.000 | 7.000 | 3.5 | 61.0 | 67.0 | 149.0 | 156.0 | 28.1 | 0.2001 | 4.96 | 10.78 | |
| 2.1350 | 1.7500 | -0.59 | 4.1929 | 0.2755 | 0.14 | 2.39 | 2.62 | 5.91 | | | | | | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952338446 |
| Diametro interno | 64.96 mm |
| Diametro esterno | 149.225 mm |
| Spessore | 54.229 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE