


## Cuscinetti conico 560-552-B-TIMKEN - 560-552-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/560-552-b-timken>

**TAPERED ROLLER BEARINGS**  
**TYPE TSF**



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Y	Dynamic <sup>(1)</sup> C <sub>01</sub>	Factors <sup>(2)</sup> C <sub>02</sub>	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N			N	N	N			
66.675	123.825	36.678	22000	0.25	1.70	9800	3430	1.09	24000	502-B	
2.6250	4.8750	1.4428	10000			1500	780		35700		

Bearing Dimensions					Shaft			Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(1)</sup>	Outer Ring Range D <sub>1</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius R <sup>(1)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. D <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>0</sub>		kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			lbs.
36.678	36.162	-4.4	138.070	6.350	3.5	77.8	84.8	116.8	91.8	21.1	0.1108		1.96
1.4440	1.1875	-0.37	5.4213	0.2500	0.14	3.02	3.31	4.57					4.31

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952338521
Diametro interno	66.675 mm
Diametro interno	2 5/8" inch
Diametro esterno	123.825 mm
Diametro esterno	4 7/8" inch
Spessore	36.678 mm
Spessore	1.444" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE