


Cuscinetti conico

47681-47620-B-TIMKEN - 47681-47620-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/47681-47620-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF



| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | | |
|--------------------|-----------|------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------------|-------|---------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Y | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | | N | | N | | | |
| 80.962 | 133.350 | 33.338 | 214000 | 0.14 | 1.48 | 30500 | 39000 | 1.44 | 362000 | 47681 | 47620-B |
| 3.1875 | 5.2800 | 1.3125 | 48100 | | | 12000 | 8640 | | 38900 | | |

| Bearing Dimensions | | | Shaft | | | | Housing | | Geometry Factors | | | Bearing Weight |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|--|------------------|----------------|----------------|----------------|
| Width B | Width C | Eff. Ctr. a ⁽³⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽⁴⁾ | Seating Shoulder Dia. d ₁ | Seating Shoulder Dia. d ₂ | Seating Shoulder Dia. D ₁ | D ₁ | D ₂ | C ₃ | kg |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | | | | lbs. |
| 33.338 | 26.166 | -4.3 | 128.811 | 5.508 | 3.3 | 88.6 | 88.6 | 128.8 | 116.4 | 29.2 | 0.1223 | 1.96 |
| 1.3125 | 1.0313 | -0.17 | 5.0652 | 0.2188 | 0.14 | 3.50 | 3.54 | 5.12 | | | | 4.18 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952339061 |
| Diametro interno | 80.962 mm |
| Diametro esterno | 133.35 mm |
| Spessore | 33.338 mm |
| Peso | 1800 g |
| Imballaggio | 1 |
| Standard | Nessuno standard |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE