


## Cuscinetti conico 677-672-B-TIMKEN - 677-672-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/677-672-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factors <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factors <sup>(2)</sup> e	Static <sup>(3)</sup> C <sub>0</sub>	Factors <sup>(2)</sup> K	Static <sup>(3)</sup> C <sub>0</sub>	Inner	Outer
mm	mm	mm	N		N		N		N		
85.725	168.275	41.275	30000	0.45	12000	0.45	8800	1.24	36000	677	672-B
3.3750	6.6250	1.6407	58000		19400		5300		20700		

Bearing Dimensions					Shaft		Housing		Geometry Factors			Bearing Weight
Width B	Width C	Eff. Ctr. a <sup>(4)</sup>	Outer Ring Range D <sub>1</sub> D <sub>2</sub>	Flange Width C <sub>1</sub>	Max Shaft File Radius R <sup>(5)</sup>	Sealing Shoulder Dia. d <sub>1</sub>	Sealing Shoulder Dia. d <sub>2</sub>	Sealing Shoulder Dia. D <sub>1</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>0</sub>	kg
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
41.275	36.162	-2.8	175.306	7.142	3.5	95.0	105.0	165.0	162.5	37.3	0.1026	4.33
1.6250	1.4193	-0.11	6.9020	0.2812	0.14	3.90	4.13	6.50				9.33

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952339214
Diametro interno	85.725 mm
Diametro interno	3 3/8" inch
Diametro esterno	168.275 mm
Diametro esterno	6 5/8" inch
Spessore	41.275 mm
Spessore	1 5/8" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE