


## Cuscinetti conico

### 52375-52630XB-TIMKEN - 52375-52630XB-TIMKEN

https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/52375-52630xb-timken

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



| Bearing Dimensions |         |         | Load Ratings                          |                          |      |                                       |                          |                       | Part Number |         |
|--------------------|---------|---------|---------------------------------------|--------------------------|------|---------------------------------------|--------------------------|-----------------------|-------------|---------|
| Bore d             | O.D. D  | Width B | Dynamic <sup>(1)</sup> C <sub>1</sub> | Factors <sup>(2)</sup> e | Y    | Dynamic <sup>(1)</sup> C <sub>2</sub> | Factors <sup>(2)</sup> K | Static C <sub>3</sub> | Inner       | Outer   |
| mm                 | mm      | mm      | N                                     |                          |      | N                                     |                          | N                     |             |         |
| 95.25              | 160.000 | 36.116  | 22200                                 | 0.44                     | 1.20 | 37900                                 | 4700                     | 34300                 | 52375       | 52630XB |
| 0.750              | 0.0025  | 0.002   | 50300                                 |                          |      | 13000                                 | 10600                    | 7000                  |             |         |

| Bearing Dimensions |         |                            |                                 |                             |  | Shaft                                |                                      |                                      | Housing        |                | Geometry Factors |                |                | Bearing Weight |
|--------------------|---------|----------------------------|---------------------------------|-----------------------------|--|--------------------------------------|--------------------------------------|--------------------------------------|----------------|----------------|------------------|----------------|----------------|----------------|
| Width B            | Width C | Eff. Ctr. g <sup>(3)</sup> | Outer Ring Range D <sub>1</sub> | Flange Width C <sub>1</sub> | Max Shaft Fillet Radius R <sup>(4)</sup> | Sealing Shoulder Dia. d <sub>1</sub> | Sealing Shoulder Dia. d <sub>2</sub> | Sealing Shoulder Dia. D <sub>1</sub> | D <sub>2</sub> | D <sub>3</sub> | C <sub>4</sub>   | C <sub>5</sub> | C <sub>6</sub> | kg             |
| mm                 | mm      | mm                         | mm                              | mm                          | mm                                       | mm                                   | mm                                   | mm                                   | mm             | mm             |                  |                |                | lbs.           |
| 36.116             | 26.195  | -4.5                       | 166.340                         | 6.350                       | 3.5                                      | 186.0                                | 112.0                                | 155.0                                | 175.4          | 41.7           | 0.1519           |                |                | 2.89           |
| 1.4219             | 1.0313  | -0.02                      | 6.5480                          | 0.2500                      | 0.14                                     | 4.13                                 | 4.41                                 | 6.10                                 |                |                |                  |                |                | 6.41           |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952339535 |
| Diametro interno | 95.25 mm      |
| Diametro esterno | 160 mm        |
| Spessore         | 36.116 mm     |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE