


## Cuscinetti conico

### 52400-52618-B-TIMKEN - 52400-52618-B-TIMKEN

https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/52400-52618-b-timken

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



| Bearing Dimensions |                   |                  | Load Ratings                             |                             |      |  |                             |                          |       | Part Number |  |
|--------------------|-------------------|------------------|--|-----------------------------|------|--|-----------------------------|--------------------------|-------|-------------|--|
| Bore<br>d          | O.D.<br>D         | Width<br>B       | Dynamic <sup>(1)</sup><br>C <sub>1</sub> | Factors <sup>(2)</sup><br>e | Y    | Dynamic <sup>(1)</sup><br>C <sub>2</sub> | Factors <sup>(2)</sup><br>K | Static<br>C <sub>0</sub> | Inner | Outer       |  |
| mm                 | mm                | mm               | N  |                             |      | N  |                             | N                        |       |             |  |
| 101.600<br>4.000   | 157.162<br>6.1875 | 36.116<br>1.4175 | 22200<br>50200                           | 0.44                        | 1.25 | 37900<br>13000                           | 47100<br>10600              | 34300<br>7000            | 52400 | 52618-B     |  |

| Bearing Dimensions |                  |                               |                                    |                                   |  | Shaft                                      |                |  | Housing        |                | Geometry Factors |                |              | Bearing Weight |
|--------------------|------------------|-------------------------------|------------------------------------|-----------------------------------|--|--|----------------|--|----------------|----------------|------------------|----------------|--------------|----------------|
| Width<br>B         | Width<br>C       | Eff. Ctr.<br>a <sup>(1)</sup> | Outer Ring<br>Range D <sub>1</sub> | Flange<br>Width<br>C <sub>1</sub> | Max Shaft<br>File Radius<br>R <sup>(1)</sup> | Sealing<br>Shoulder Dia.<br>d <sub>1</sub> | d <sub>2</sub> | Sealing<br>Shoulder Dia.<br>D <sub>1</sub> | D <sub>2</sub> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>3</sub> |              |                |
| mm                 | mm               | mm                            | mm                                 | mm                                | mm   | mm   | mm             | mm   | mm             |                |                  |                | kg           |                |
| 36.116<br>1.4219   | 36.196<br>1.4213 | -4.5<br>-0.02                 | 168.910<br>6.6475                  | 6.200<br>0.2400                   | 3.5<br>0.14                                  | 111.0<br>4.37                              | 117.0<br>4.61  | 155.8<br>6.10                              |                | 175.4          | 41.7             | 0.1519         | 2.47<br>0.44 |                |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952339740 |
| Diametro interno | 101.6 mm      |
| Diametro esterno | 157.162 mm    |
| Spessore         | 36.116 mm     |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE