


## Cuscinetti conico

### EE203136-203190-B-TIMKEN - EE203136-203190-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/ee203136-203190-b-timken>

**TAPERED ROLLER BEARINGS**

**TYPE TSF**



| Bearing Dimensions |          |             | Load Ratings                    |                               |      |                                    |                               |                 |          | Part Number |  |
|--------------------|----------|-------------|---------------------------------|-------------------------------|------|------------------------------------|-------------------------------|-----------------|----------|-------------|--|
| Bore $d$           | O.D. $D$ | Width $T_1$ | Dynamic <sup>(1)</sup><br>$C_1$ | Factors <sup>(2)</sup><br>$e$ | $Y$  | Dynamic <sup>(1)</sup><br>$C_{10}$ | Factors <sup>(2)</sup><br>$K$ | Static<br>$C_0$ | Inner    | Outer       |  |
| mm                 | mm       | mm          | N                               |                               |      | N                                  |                               | N               |          |             |  |
| 346.075            | 482.200  | 36.512      | 102000                          | 0.14                          | 1.44 | 20600                              | 10500                         | 177000          | EE203136 | 203190-B    |  |
| 13.675             | 19.000   | 1.4375      | 23100                           |                               |      | 5900                               | 4270                          | 30600           |          |             |  |

| Bearing Dimensions |           |                     |                             |                    |                                   | Shaft                       |                             | Housing                     |                             | Geometry Factors |       |        | Bearing Weight |
|--------------------|-----------|---------------------|-----------------------------|--------------------|-----------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|------------------|-------|--------|----------------|
| Width $B$          | Width $C$ | Eff. Ctr. $a^{(3)}$ | Outer Ring Range D.L. $D_1$ | Flange Width $C_2$ | Max Shaft Fillet Radius $R^{(4)}$ | Sealing Shoulder Dia. $d_1$ | Sealing Shoulder Dia. $d_2$ | Sealing Shoulder Dia. $D_1$ | Sealing Shoulder Dia. $D_2$ | $G_1$            | $G_2$ | $C_3$  | kg             |
| mm                 | mm        | mm                  | mm                          | mm                 | mm                                | mm                          | mm                          | mm                          | mm                          |                  |       |        | mm             |
| 63.500             | 44.450    | 16.3                | 486.700                     | 14.200             | 6.5                               | 386.0                       | 376.0                       | 486.0                       | 486.0                       | 2136.1           | 238.0 | 0.1778 | 28.58          |
| 2.500              | 1.700     | 0.64                | 18.558                      | 0.5625             | 0.27                              | 14.41                       | 14.80                       | 18.38                       | 18.38                       |                  |       |        | 73.14          |

## CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952340784 |
| Diametro interno | 346.075 mm    |
| Diametro esterno | 482.6 mm      |
| Spessore         | 63.5 mm       |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE