

Cuscinetti conico

EE244180-EE244235-B-TIMKEN - EE244180-EE244235-B-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/ee244180-ee244235-b-timken>

TAPERED ROLLER BEARINGS

TYPE TSF

| Bearing Dimensions | | | Load Ratings | | | | | | Part Number | |
|--------------------|-----------|------------|--|-----------------------------|--|-----------------------------|--------------------------|---------|-------------|---------|
| Bore d | O.D. D | Width B | Dynamic ⁽¹⁾ C ₁ | Factors ⁽²⁾ e | Dynamic ⁽¹⁾ C ₂ | Factors ⁽²⁾ K | Static C ₀ | Inner | Outer | |
| mm | mm | mm | N | | N | | N | | | |
| 457.200 | 596.900 | 73.025 | 1410000 | 0.14 | 307000 | 20400 | 1.04 | 2000000 | EE244180 | 20420-B |
| 18.000 | 23.500 | 3.000 | 318000 | | 62400 | 5700 | | 640000 | | |

| Bearing Dimensions | | | Shaft | | Housing | | Geometry Factors | | | Bearing Weight | | |
|--------------------|------------|-------------------------------|--|-----------------------------------|--|--|--|----------------|----------------|----------------|--------|--------|
| Width B | Width C | Eff. Ctr. a ⁽¹⁾ | Outer Ring Range D ₁ D ₂ | Flange Width C ₁ | Max Shaft File Radius R ⁽¹⁾ | Sealing Shoulder Dia. d ₁ | Sealing Shoulder Dia. D ₁ | G ₁ | G ₂ | C ₃ | kg | |
| mm | mm | mm | mm | mm | mm | mm | mm | | | | lbm | |
| 73.025 | 53.975 | 26.7 | 611.200 | 14.200 | 0.7 | 498.0 | 494.0 | 376.0 | 441.0 | 227.1 | 0.2203 | 55.04 |
| 2.8750 | 2.1250 | 1.05 | 24.0630 | 0.5630 | 0.38 | 19.42 | 19.45 | 22.47 | | | | 122.51 |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952340937 |
| Diametro interno | 457.2 mm |
| Diametro esterno | 596.9 mm |
| Spessore | 73.025 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE