

Gusci a rullini TAM1215-IKO - TAM1215-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/tam1215-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number												
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g			
12	---	---	---	---	---	---	---	---	---	---			
								TAM 1215	14	---			
Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring		
F_w	D	C	f_2 Max.	Shaft dia. H7		Housing bore dia. H7		N	N	rpm	IRT		
				Max.	Min.	Max.	Min.						
12	19	15	1.3	12.000	11.989	19.012	18.991	---	---	7 440	8 320	35 000	IRT 815

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952352008
Diametro interno	12 mm
Diametro interno	0.472" inch
Diametro esterno	19 mm
Diametro esterno	0.748" inch
Spessore	15 mm
Spessore	0.591" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE