

## Cuscinetti conico 390A-394D-TIMKEN - 390A-394D-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/390a-394d-timken>

**TAPERED ROLLER BEARINGS**  
DOUBLE-ROW • TYPE TDO

**TYPE TDO**

Bearing Dimensions				Load Ratings							
Bore d	O.D. D	Width T	Double Outer Ring Width C	Dynamic <sup>(1)</sup>		Static <sup>(1)</sup>		Dynamic <sup>(1)</sup>		Factor <sup>(1)</sup>	
mm	mm	mm	mm	C <sub>10</sub>	N	Y <sub>1</sub>	Y <sub>2</sub>	C <sub>0</sub>	N	C <sub>02</sub>	K
63.500	110.000	52.388	46.838	32000	17200	0.40	1.88	2.50	29000	17000	1.45
2.500	4.3007	2.0625	1.8125	38700	18700				5700	3570	

  

Part Number		Dimensions						Pin		Geometry Factors			Bearing Weight
Inner	Outer	Max. Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>2</sub>	Max. Housing Fillet Radius r <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	K <sub>1</sub>	K <sub>2</sub>	G <sub>1</sub>	G <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>		
390A	394D	1.5 0.06	73.0 2.87	0.8 0.05	106.4 4.11	-	-	50.0	21.4	0.0084		1.88 4.18	

### CARATTERISTICHE DEL PRODOTTO

Marchio	TIMKEN
N° Ean13	3663952356983
Diametro interno	63.5 mm
Diametro esterno	110 mm
Spessore	52.388 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE