



Gusci a rullini TAW6045-Z-IKO - TAW6045-Z-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/taw6045-z-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS

TA--Z TLA--Z

Shaft dia. mm	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
60	TAW 6045 Z	270	—	—	—	—	—	—	—

Boundary dimensions mm	Standard reporting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring			
	F _w	D	C	t ₂ Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.							
60	72	45	3.4	60.000	59.981	72.018	71.988	—	—	85 400	193 000	5 000	IRT 5045

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952357423
Diametro interno	60 mm
Diametro esterno	72 mm
Spessore	45 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE