


Gusci a rullini TAM5030-IKO - TAM5030-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/tam5030-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
50			TAM	5030	178					

Boundary dimensions mm		Standard mounting dimensions mm						Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	f ₂ Max.	Shaft dia. H7 Max. Min.	Housing bore dia. H7 Max. Min.	N7 Min.	N	N	rpm	IRT 4530		
50	62	30	3.4	50.000	49.984 62.018	61.988	—	—	59 500	114 000	6 500	IRT 4530

Note(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952357461
Diametro interno	50 mm
Diametro interno	1.969" inch
Diametro esterno	62 mm
Diametro esterno	2.441" inch
Spessore	30 mm
Spessore	1.181" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE