

Cuscinetti conico

52375-52637D-TIMKEN - 52375-52637D-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/52375-52637d-timken>

TAPERED ROLLER BEARINGS
DOUBLE-ROW • TYPE TDO

TYPE TDO

| Bearing Dimensions | | | | Load Ratings | | | | | | | | |
|--------------------|---------|---------|---------------------------|------------------------|-------|-----------------------|----------------|------------------------|-----------------|-----------------------|--------|------|
| Bore d | O.D. D | Width T | Double Outer Ring Width C | Dynamic ⁽¹⁾ | | Static ⁽¹⁾ | | Dynamic ⁽¹⁾ | | Factor ⁽¹⁾ | | |
| mm | mm | mm | mm | C ₁₀ | C | Y ₁ | Y ₂ | C ₉₀ | C ₅₀ | C ₁₀₀ | K | |
| 95.250 | 161.925 | 82.547 | 61.912 | 30600 | 87500 | 0.47 | 1.42 | 2.12 | 57000 | 47100 | 100000 | 1.23 |
| 3.7500 | 6.3750 | 3.2488 | 2.4375 | 87500 | 87500 | | | | 130000 | 108000 | 227000 | |

| Part Number | | Shaft | | | | Housing | | | | Pin | | Geometry Factors | | | Bearing Weight |
|-------------|--------|---|--------------------------------------|---|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|------|-------|----------------|
| Inner | Outer | Max. Shaft Fillet Radius R ₁ | Backing Shoulder Dia. d ₁ | Max. Housing Fillet Radius r ₁ | Backing Shoulder Dia. D ₁ | K ₁ | K ₂ | G ₁ | G ₂ | C ₁ | C ₂ | | | | |
| mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | mm | |
| 52375 | 52637D | 3.5 0.14 | 112.8 4.41 | 8.8 0.33 | 156.8 6.08 | - | - | - | - | 125.4 | 41.7 | 0.1019 | 0.48 | 14.33 | |

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | TIMKEN |
| N° Ean13 | 3663952358741 |
| Diametro interno | 95.25 mm |
| Diametro esterno | 161.925 mm |
| Spessore | 82.547 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE