


Gusci a rullini YB2-5-4-IKO - YB2-5-4-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb2-5-4-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
3.969 ($\frac{3}{16}$)	—	—	—	—	YB 2.5 4	0.96	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C_0	rpm	
3.969 $\frac{3}{16}$	7.144 $\frac{1}{2}$	6.35 .250	Max. 3.969 Min. 3.961	Max. 7.152 Min. 7.137	2 320	2 440	40 000	—	—	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361192
Diametro interno	3.969 mm
Diametro esterno	7.144 mm
Spessore	6.35 mm
Peso	96 g
Imballaggio	1
Standard	Nessuno standard

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE