

Gusci a rullini
YB66-IKO - YB66-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb66-iko>

**SHELL TYPE NEEDLE ROLLER BEARINGS**
Inch Series



Shaft dia.		Identification number							
mm (inch)	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Mass (Grease retained) (Ref.) g
9.525 (3/8)	—	—	—	—	YB 66	5.3	—	—	—

Boundary dimensions mm (inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h8	Housing bore dia. J7	Max.	Min.	C	C_0	rpm	
9.525 (3/8)	14.288 (1/2)	9.52 (3/8)	9.525	9.516	14.298	14.280	6 920	9 410	16 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361246
Diametro interno	9.525 mm
Diametro esterno	14.288 mm
Spessore	9.52 mm
Peso	18 g
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE