


## Gusci a rullini YB98-IKO - YB98-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb98-iko>

IKO  
SHELL TYPE NEEDLE ROLLER BEARINGS  
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ( $\frac{9}{16}$ )	—	—	—	—	—	—	—	—	YB 98 10.1
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	$b_2$	Shaft dia. $h_8$	Housing bore dia. $J_7$	$C$	$C_0$	rpm	
14.288   $\frac{9}{16}$	19.050   $\frac{3}{4}$	12.70   500	—	14.288   Max. Min.	14.277   19.062   19.041   Max. Min.	11 600   N	20 400   N	11 000	IRB 68

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361604
Diametro interno	14.288 mm
Diametro esterno	19.05 mm
Spessore	12.7 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE