


Gusci a rullini BHAM1212-IKO - BHAM1212-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham1212-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 (3/4)	—	—	—	—	—	—	—	BHAM 1212	28.5	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	Max. Min.	N	N	rpm	IRB 812-1	
19.050 3/4	26.988 1 1/4	19.05 .750 1.3	19.050 19.037	27.000 26.979	16 600	22 600	20 000				

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361819
Diametro interno	19.05 mm
Diametro esterno	26.988 mm
Spessore	19.05 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE