


Gusci a rullini YB124-IKO - YB124-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb124-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end										
19.050 (3/4)	—	—	—	—	—	—	—	—	—	—	—	YB 124	8.5
Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring				
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	C								
19.050 25.400	25.400 6.35 250	—	19.050 19.037 25.412 25.391	—	7 820	10 200	8 000	—					

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952361826
Diametro interno	19.05 mm
Diametro esterno	25.4 mm
Spessore	6.35 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE