

Gusci a rullini BHAM1616-IKO - BHAM1616-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham1616-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series

Shaft dia. mm (inch)	Identification number								Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g				
25.400 (1)	—	—	—	—	—	—	—	—	BHAM 1616	48	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C		Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	Basic dynamic load rating C		Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring			
25.400	33.338	25.40(1.000)	25.400 25.387	33.352 33.327	26 400		44 500	15 000	IRB 1216			

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362038
Diametro interno	25.4 mm
Diametro esterno	33.338 mm
Spessore	25.4 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE