

Gusci a rullini
YB1612-IKO - YB1612-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/yb1612-iko>



SHELL TYPE NEEDLE ROLLER BEARINGS

Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g	Mass (Ref.) g																	
	Standard	Mass (Ref.) g	Closed end																											
25.400 (1)	—	—	—	—	—	—	—	—	—	—	—	YB 1612	34.5																	
Boundary dimensions mm(inch)																														
F _w			D			C			Shaft dia. h ₈			Housing bore dia. j ₇			Basic dynamic load rating C ₁₀		Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾		Assembled inner ring									
Max.			Min.			Max.			Min.			Max.		Min.		N		N		rpm		IRB 1212								
25.400			31.750			19.05			750			—			25.400		25.387		31.764		31.739		28 200		58 000		6 000		IRB 1212	

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362052
Diametro interno	25.4 mm
Diametro esterno	31.75 mm
Spessore	19.05 mm
Imballaggio	1

contatto@123cuscinetti.ch
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE