


Gusci a rullini BHAM2020-IKO - BHAM2020-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bham2020-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
31.750 (1 1/4)	—	—	—	—	—	—	—	BHAM 2020	86.5	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynam. load rating	Basic static load rating	Allowable rotational speed ^(*)	Assembled inner ring
F_w	D	C_0	Shaft dia. d_s	Housing bore dia. J_7	Max.	Min.	C	C_0	rpm	IRB 1620
31.750 (1 1/4)	41.275 (1 1/2)	31.75 (1.250)	3.4	31.750	31.734	41.289	41.264	40 000	69 600	12 000

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952362335
Diametro interno	31.75 mm
Diametro esterno	41.275 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE