


Gusci a rullini BAM228-IKO - BAM228-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/bam228-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g																																												
	Standard	Mass (Ref.) g	Closed end																																																					
34.925 (1 3/8)	---	---	---	---	---	---	---	---	---	---	---	---																																												
<table border="1"> <thead> <tr> <th colspan="3">Boundary dimensions</th> <th colspan="4">Standard mounting dimensions</th> <th>Basic dynam.</th> <th>Basic static</th> <th>Allowable</th> <th>Assembled</th> </tr> <tr> <th>F_w</th> <th>D</th> <th>C</th> <th>Shaft dia. h_8</th> <th>Housing bore dia. $J7$</th> <th>Max.</th> <th>Min.</th> <th>load rating C</th> <th>load rating C_0</th> <th>rotational speed^(*)</th> <th>inner ring</th> </tr> <tr> <th>mm</th> <th>mm</th> <th>mm</th> <th>mm</th> <th>mm</th> <th>mm</th> <th>mm</th> <th>N</th> <th>N</th> <th>rpm</th> <th>IRB 188</th> </tr> </thead> <tbody> <tr> <td>34.925</td> <td>41.275</td> <td>12.70</td> <td>34.925</td> <td>34.909</td> <td>41.289</td> <td>41.264</td> <td>9 770</td> <td>16 600</td> <td>10 000</td> <td>IRB 188</td> </tr> </tbody> </table>													Boundary dimensions			Standard mounting dimensions				Basic dynam.	Basic static	Allowable	Assembled	F_w	D	C	Shaft dia. h_8	Housing bore dia. $J7$	Max.	Min.	load rating C	load rating C_0	rotational speed ^(*)	inner ring	mm	mm	mm	mm	mm	mm	mm	N	N	rpm	IRB 188	34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188
Boundary dimensions			Standard mounting dimensions				Basic dynam.	Basic static	Allowable	Assembled																																														
F_w	D	C	Shaft dia. h_8	Housing bore dia. $J7$	Max.	Min.	load rating C	load rating C_0	rotational speed ^(*)	inner ring																																														
mm	mm	mm	mm	mm	mm	mm	N	N	rpm	IRB 188																																														
34.925	41.275	12.70	34.925	34.909	41.289	41.264	9 770	16 600	10 000	IRB 188																																														

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952363035
Diametro interno	34.925 mm
Diametro esterno	41.275 mm
Spessore	12.7 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE