


Cuscinetti a rullini GBRI82012-IKO - GBRI82012-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri82012-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
12.700 (.50)	GBRI 82012	86.5	12.700 ⁽¹⁾ ₀	31.750 ⁽¹⁾ ₀	19.050 ⁽¹⁾ ₀	19.300	19.050 ⁽¹⁾ ₀
Standard mounting dimensions mm		Ball diam. mm C	Basic load rating N	Dynamic load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
d _a Min.	d _a Max.					D _a Max.	r _{as max} (°)
17.5	18	27	0.6	26 400	34 500	8 000	LRBZ 81212

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377384
Diametro interno	12.7 mm
Diametro esterno	31.75 mm
Spessore	19.05 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE