


Cuscinetti a rullini GBRI122412-IKO - GBRI122412-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri122412-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
19.050 ($\frac{3}{4}$)	GBRI 122412	112	19.050 _{J0}	38.100 _{J0}	19.050 _{J0}	19.300	25.400 _{J0}
Standard mounting dimensions mm		Ball diam. mm C	Basic load rating N	Limiting load rating N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring	
d _s Min.	d _s Max.					D _s Max.	r _{as max} (²)
24	24.4	33.3	0.6	31 000	46 100	6 000	LRBZ 121612

Notes: ⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is preapplied. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377414
Diametro interno	19.05 mm
Diametro esterno	38.1 mm
Spessore	19.3 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE