


Cuscinetti a rullini GBRI183016-IKO - GBRI183016-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri183016-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F_w
28.575 (1 1/8)	GBRI 183016	200	28.575 \pm 0.015	47.625 \pm 0.025	25.400 \pm 0.025	25.650	34.925 \pm 0.025
Standard mounting dimensions mm		Basic dynamic load rating C_0 N	Limiting static load rating C_0 N	Allowable rotational speed ^(*) rpm	Assembled inner ring		
d_a Min.	D_a Max.				$r_{as max}$ ([†])		
33.5	33.9	42.8	0.6	49 500	91 800	4 500	LRBZ 182216

Notes: ^(†) Maximum permissible corner radius of the housing.
^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377452
Diametro interno	28.575 mm
Diametro interno	1 1/8" inch
Diametro esterno	47.625 mm
Diametro esterno	1 7/8" inch
Spessore	25.65 mm
Spessore	1.01" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE