


Cuscinetti a rullini GBRI223516-IKO - GBRI223516-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri223516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			d	D	C	B	F _w
34.925 (1 3/8)	GBRI 223516	255	34.925 (1 3/8)	55.562 (2 1/8)	25.400 (1)	25.650	41.275 (1 1/2)
Standard mounting dimensions mm		Basic dynamic load rating C ₀ N	Limiting load rating C ₀ N	Allowable rotational speed (1) rpm	Assembled inner ring		
d _a Min.	D _a Max.				r _{as max} (°)		
40.2	40.2	50.5	0.6	56 600	105 000	3 500	LRBZ 222616

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377483
Diametro interno	34.925 mm
Diametro interno	1 3/8" inch
Diametro esterno	55.562 mm
Diametro esterno	2 3/16" inch
Spessore	25.65 mm
Spessore	1.01" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE