

## Cuscinetti a rullini GBR122012-IKO - GBR122012-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr122012-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ( <sup>(1)</sup> ) Max.	
			F	D	C	D <sub>s</sub>	r as max
<b>19.050</b> ( <sup>(3)</sup> 3/4)	<b>GBR 122012</b>	63	19.050 <sup>(1)</sup> <sub>0</sub>	31.750 <sup>(1)</sup> <sub>0</sub>	19.050 <sup>(1)</sup> <sub>0</sub>	27	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>					
N	N	rpm					
26 400	34 500	8 000					

Notes:  
(1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks:  
1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377704
Diametro interno	19.05 mm
Diametro esterno	31.75 mm
Spessore	19.05 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE