

Cuscinetti a rullini GBR142212-IKO - GBR142212-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr142212-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series

| Shaft dia. mm (inch) | Identification number | Mass (ref.) g | Boundary dimensions mm(inch) | | | Standard mounting dimensions mm ⁽¹⁾ | |
|-------------------------------------|---|---|------------------------------|--------------------------|-----------------------|---|---------------------|
| | | | F | D | C | D _s Max. | r _{as max} |
| 22.225 ($\frac{9}{16}$) | GBR 142212 | 71 | 22.225 ⁽²⁾ | 34.925 ⁽¹⁾⁽²⁾ | 19.050 ⁽²⁾ | 30 | 0.6 |
| Basic dynamic load rating C | Basic static load rating C ₀ | Allowable rotational speed ⁽³⁾ | | | | | |
| N | N | rpm | | | | | |
| 28 600 | 40 100 | 7 000 | | | | | |

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952377711 |
| Diametro interno | 22.225 mm |
| Diametro esterno | 34.925 mm |
| Spessore | 19.05 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE