


## Cuscinetti a rullini GBR162412-IKO - GBR162412-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr162412-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (1)	
			F	D	C	D <sub>s</sub> Max.	R <sub>as max</sub>
<b>25.400</b> (1)	<b>GBR 162412</b>	79	25.400 <sub>0</sub>	38.100 <sub>0.012</sub>	19.050 <sub>0.002</sub>	33.3	0.6
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed(2)					
N	N	rpm					
31 000	46 100	6 000					

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-packed. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377735
Diametro interno	25.4 mm
Diametro esterno	38.1 mm
Spessore	19.05 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE