


Cuscinetti a rullini GBR303920-IKO - GBR303920-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbr303920-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm (⁽¹⁾)	
			F _o	D	C	D _s Max.	r _{as} max
47.625 (1 7/8)	GBR 303920	250	47.625 (⁽²⁾)	61.912 (⁽²⁾)	31.750 (⁽²⁾)	56.2	1
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽³⁾					
N	N	rpm					
72 400	150 000	3 000					

Notes:⁽¹⁾ Maximum permissible corner radius of the housing.
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks:
2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-packed. Perform proper lubrication.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377841
Diametro interno	47.625 mm
Diametro esterno	61.912 mm
Spessore	31.75 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE