


## Cuscinetti a rullini GBRI446832-IKO - GBRI446832-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/gbri446832-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (Ref.) g	Boundary dimensions mm(inch)				
			<i>d</i>	<i>D</i>	<i>C</i>	<i>B</i>	<i>F<sub>w</sub></i>
<b>69.850</b> (2 3/4)	<b>GBRI 446832</b>	1 840	69.850 (2 3/4)	107.950 (4 1/4)	50.800 (2)	51.050	82.550 (3 1/4)

Standard mounting dimensions mm		Basic dynamic load rating <i>C</i> N	Static load rating <i>C<sub>0</sub></i> N	Allowable rotational speed (1) rpm	Assembled inner ring
<i>d<sub>a</sub></i> Min.	<i>D<sub>a</sub></i> Max.				
77	79	214 000	452 000	1 800	<b>LRBZ 445232</b>

Notes: (1) Maximum permissible corner radius of the housing.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. No grease is pre-applied. Perform proper lubrication.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952377964
Diametro interno	69.85 mm
Diametro esterno	107.95 mm
Spessore	50.8 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE