


Cuscinetti a rullini RNA4900-U-IKO - RNA4900-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna4900-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_a (1)
14	---	RNA 4900U	---	---	16.3	14	22	13	0.3
Standard rounding dimension D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
	N	N	rpm						
Notes (1) (2)	20	8 080	8 490	14 000					
Remarks:	Minimum allowable value of chamfer dimension r . Allowable rotational speed applies to grease lubrication. The outer ring has an oil groove and an oil hole. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.								

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952378787
Diametro interno	14 mm
Diametro esterno	22 mm
Spessore	13 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE