


Cuscinetti a rullini RNA6907-U-IKO - RNA6907-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6907-u-iko>

IKO

MACHINED TYPE NEEDLE ROLLER BEARINGS

With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F _w	D	C	7 _s (1)
42	—	—	—	—	200	42	55	36	0.6
Standard mounting diameter D _s max. mm									
	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed (2)						
	N	N	rpm						
	51 600	92 600	4 500						

Notes: 1) Minimum allowable value of chamfer dimension r.
2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379197
Diametro interno	42 mm
Diametro esterno	55 mm
Spessore	36 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE