


Cuscinetti a rullini RNA4910-U-IKO - RNA4910-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna4910-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
58	---	RNA 4910U	---	---	177	58	72	22	0.6
Standard rounding dimension D_s Max. mm		Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (reference speed) rpm					
68		41 300	71 100	3 500					

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379357
Diametro interno	58 mm
Diametro interno	2.283" inch
Diametro esterno	72 mm
Diametro esterno	2.835" inch
Spessore	22 mm
Spessore	0.866" inch
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE