


Cuscinetti a rullini RNA6911-U-IKO - RNA6911-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6911-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



| Shaft dia. mm | Identification number | | | | Mass (Ref) g | Boundary dimensions mm | | | |
|--|-------------------------------|--------------------------------|--------------------------------|---------------|--------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 63 | — | — | — | RNA 6911U | 470 | 63 | 80 | 45 | 1 |
| Standard mounting dimension D_s Max. mm | | | | | | | | | |
| | Basic dynamic load rating C | Basic static load rating C_0 | Allowable rotational speed (2) | | | | | | |
| 75 | 89 400 | 171 000 | 3 000 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | IKO |
| N° Ean13 | 3663952379432 |
| Diametro interno | 63 mm |
| Diametro esterno | 80 mm |
| Spessore | 45 mm |
| Imballaggio | 1 |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE