

## Cuscinetti a rullini RNA6912-U-IKO - RNA6912-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6912-u-iko>



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	D	C	$r_s$ (1)
68	—	—	—	RNA 6912U	505	68	85	45	1
Standard mounting diameter $D_s$ Max. mm		Basic dynamic load rating C	Basic static load rating $C_0$	Allowable rotational speed (2)					
80		93 400	186 000	3 000					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379494
Diametro interno	68 mm
Diametro esterno	85 mm
Spessore	45 mm
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE