

Cuscinetti a rullini RNA6917-UU-IKO - RNA6917-UU-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/rna6917-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (*)
100	—	—	RNA 6917UU	—	1 300	100	120	63	1.1
Standard mounting dimension D_s Max. mm	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾						
113.5	168 000	448 000	1 900						

Notes: (*) Minimum allowable value of chamfer dimension r .
(1) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952379753
Diametro interno	100 mm
Diametro esterno	120 mm
Spessore	63 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE