

Cuscinetti a rullini NA4900-U-IKO - NA4900-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na4900-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
10	—	NA 4900U	—	—	24.5	10	22	13	14

r_s min (1)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 101414
		Min.	Max.	d_s			
0.3	14	12	13	20	8 080	8 490	14 000

Notes:
(1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381060
Diametro interno	10 mm
Diametro esterno	22 mm
Spessore	14 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE