


Cuscinetti a rullini NA4901-U-IKO - NA4901-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na4901-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
12	—	NA 4901U	—	—	27.5	12	24	13	14

r _s min (1)	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Basic dynamic load rating C ₁₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 121614
		d _s Min.	d _s Max.				
0.3	16	14	15	22	8 470	9 320	12 000

Notes: (1) Minimum allowable value of shaft dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381077
Diametro interno	12 mm
Diametro esterno	24 mm
Spessore	14 mm
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE