


## Cuscinetti a rullini NA6906-U-IKO - NA6906-U-IKO

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rullini/rullini/na6906-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
30	—	—	—	—	NA 6906U	185	30	47	30	31

$r_s$ min (1)	$F_w$	Standard mounting dimensions mm		Basic static load rating $C_0$ N	Basic dynamic load rating $C$ N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring	
		Min.	Max.					
0.3	35	32	34	45	40 100	63 000	5 500	LRTZ 303531

Notes:  
(1) Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark:  
1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

## CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952381398
Diametro interno	30 mm
Diametro interno	1.181" inch
Diametro esterno	47 mm
Diametro esterno	1.85" inch
Spessore	31 mm
Spessore	1.22" inch
Imballaggio	1

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE